

GMI LM2MC Overlamine
2.0 Mil Matte Clear Cast Vinyl
With UV Protection



Offering maximum flexibility, the matte finish of the cast vinyl film reduces glare and still provides an excellent view of the underlying image. The stabilized vinyl film offers excellent protection from UV radiation. The overlamine adhesive wets out quickly to provide a clean image.

CONSTRUCTION

Applications	Used for overlaminating printed vinyl films.
Face Film	2.0 Mil
Adhesive Release	20 min. 32 oz./in. 24 hrs. 50 oz/in.
Liner	50 # white kraft

PHYSICAL PROPERTIES

Outdoor Durability	5 years.
Minimum Surface/Ambient Air Application Temperature	+ 50° F.
Adhesive	Permanent acrylic
Application Surface	+ 50° F.
Service Temperature Range	- 50° F. to 225° F.
Opacity	Clear.
Product Thickness	2.0 Mil
Chemical Resistance	Distilled water (24 hrs.) no effect; Detergent (24 hrs.) no effect; Gasoline (10 minutes) no effect.
Water Resistance	Excellent.
Finish	Matte.
Shelf Life	@ 73, 50 % RH

Sizes	LM2MC2425	24" X 25 YDS
	LM2MC2450	24" X 50 YDS
	LM2MC3025	30" X 25 YDS
	LM2MC3050	30" X 50 YDS
	LM2MC3625	36" X 25 YDS
	LM2MC3650	36" X 50 YDS
	LM2MC4825	48" X 25 YDS
	LM2MC4850	48" X 50 YDS
	LM2MC5425	54" X 25 YDS
	LM2MC5450	54" X 50 YDS
	LM2MC6025	60" X 25 YDS
	LM2MC6050	60" X 50 YDS

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2008 Graphic Materials International.
 All rights reserved. LM2MC 082808.