

GMI Series 7530 PhotoLuminescent Film
Safety Grade Glow-In-The-Dark • Up to 10+ Hours



Flexible laminated film coated with permanent acrylic pressure-sensitive adhesive and backed with a poly coated release liner. Safety grade photoluminescent material is designed to glow 10+ hours. Product withstands UV-light and does not show significant degradation when used outdoors.

CONSTRUCTION

Applications	All types of safety Signs Identify doors, walkway directions, exit doors, hazardous areas, fire equipment, escape route instructions
Face Film	Flexible .010 Laminated Film
Mil/Durability	Film with adhesive .010 +/- 10%
Adhesive Release	PSTC-7 Shear adhesion from stainless steel (1/2" x 1/2", 500 grams) <24 hours
Liner	.005 ± 10%

PHYSICAL PROPERTIES

Print Methods	Thermal, digital and screenprinting processes.
Recharge Time	5 minutes to most light sources.
Minimum Surface/Ambient Air Application Temperature	50° F.
Test Standards	EN71 (Passed)
Product Color	White/Green
Emission Color	Yellow/Green
Typical Film Caliper (w/Adhesive)	.010 ± 10%
UV Stability	Excellent.
Adhesion	From stainless steel 1/2" x 1/2", 500 grams > 24 hours.
Shelf Life	Up to one year
Sizes	27" X 25 FT 54" X 25 FT 27" X 50 FT 54" X 50 FT 27" X 150 FT 54" X 150 FT

Longer lengths available upon requests.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



If the size you require is not listed, please call GMI Inside Sales **800-388-1161**.



Visit www.gmintl.com for downloadable ICC profiles for your specific printer and ink set.

©2007 Graphic Materials International.
All rights reserved. 7530 073007