

SPMMAG Flexible Magnetics
12.0, 20.0 AND 30.0 Mil

For Eco-Solvent and Solvent-Based Inkjet Printers



Lead-free flexible magnetic vinyl.

CONSTRUCTION

Applications	Ideal uses include car signs, business cards, promotional products, message boards and other promotional point-of-purchase displays and advertising specialties.
Face Film	Matte White Vinyl Film
Release Liner	None

PHYSICAL PROPERTIES

Outdoor Durability	Up to 3 years
Print Methods	Silk screen, foil hot stamping, label, offset and digital printing processes
Minimum Surface/Ambient Air Application Temperature	60° F
Magnetization	Multi-pole magnetization. Magnetic strength at or above .020 Mil thickness is ample for car signs.
Service Temperature Range	60° F +
Opacity	Excellent.
Product Thickness	12 mil = .30 mm 20 mil = .51 mm 30 mil = .76 mm
Minimum Magnetic Pull/lbs. per sq. ft. (kg per m2)**	12 mil = 30 (146) 20 mil = 60 (293) 30 mil = 85 (415)
Water Resistance	Yes.
Shelf Life	2 Years
Sizes	24" X 10 FT 24" X 25 FT 24" X 50 FT

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

If the size you require is not listed, please call Inside Sales **800-333-3136**.

©2012 Catalina Graphic Films. All rights reserved. SPMMAG 01182012.